



Order no.: 068181

Roof parapet bridge V2A stainless steel

Specification

| Length | Entry/Exit | Material | Passage width | Clear length |
|--|-------------------------------|--|---------------------|--------------|
| 1 m | Roof parapet bridge | Stainless steel | 536 mm | 880 mm |
| Transport dimensions 2220 x 1000 x 590 mm, 61.7 kg | Predecessor product 068181 | Business division MUNK Günzburger Steigtechnik | Order no. 068181 | |

Facts

- With grating
- Passage width 536 mm, special widths on request
- Recommendation for the bottom end at the exit point: Adjustable wall anchors or foot plates
- Descent ladder: Length 1,220 mm, Length to be cut to size by client

Scope of supply

■ Grating: 1 x

■ Garde-corps: 2 x

Descent ladder: 1 x

Assembly kit: 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001

■ Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria







