



Order no.: 040270

Stepladder with steps, double-sided access, pluggable



Number of steps

4

Specification

| Working height 2.45 m | Step design Steps | Number of steps/rungs 4 steps | Step depth 80 mm | Step/Rung distance 235 mm |
|-----------------------------------------------------------|------------------------------|----------------------------------|------------------------------------------------------|-------------------------------------------------------|
| Type of non-slip protection Aluminium corrugated | Height 909 mm | Base spread 857 mm | Inclination 70 ° | Lower outer width 462 mm |
| Depth of side-rails 73 mm | Width of side-rails 25 mm | Max. load capacity 150 kg | Design type Freestanding Double-sided access | Transport dimensions 990 x 460 x 212 mm, 7.8 kg |
| Business division MUNK Günzburger Steigtechnik | Order no. 040270 | | | |

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- ergo-pad® grip area with clamping mechanism



- 4-fold bolted, solid ladder joint made of aluminium
- nivello® ladder shoes with patented 2-axis inclination technology
- Can optionally be equipped with clip-step step padding, clip-step R13 and clip-step relax
- Space-saving transport and storage
- Flexible means of extension thanks to optional push-fit section
- Ladder inclination: 70°
- Spreader lock with two high-strength polyester straps

Step spacing: 235 mmMaximum load: 150 kg

Scope of supply

Ladder: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability





ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





Corporate certifications

on sustainability criteria







