



Order no.: 036108

2-section rung push-up
extension ladder made of
glass-fibre reinforced
plastic without stabiliser



Number of rungs

2x8

2x10

2x12

Specification

Working height 5.2 m	Step design Rungs	Number of steps/rungs 2x 8 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Retracted length 2.5 m	Extended length 4.18 m	Outer width 420 mm	Depth of side-rails 73 mm
Width of side-rails 25 mm	Design type To lean against 2- part	Weight 15.5 kg	Transport dimensions 2480 x 428 x 143 mm, 15.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 036108	Price € 1,032.00			

Facts

- Rung push-up extension ladder made of glass-fibre reinforced plastic
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Galvanised steel fittings
- Easy height adjustment from rung to rung
- Upper ladder from size 2x12 rungs with wall castors
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- nivello® ladder shoes with patented 2-axis inclination technology
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Push-up extension ladder tested in accordance with DIN EN 131. The design takes into account EN 61478:2002 (Cat. 1: 28,000 V)
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade


Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



The movable ladder shoe sets new standards in stability

[Learn more](#)



Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548

