



Order no.: 041103

# Single-sided stepladder with castors



Number of steps

3	4	5	6	7	8	9	10	12
14								

## Specification

Working height 2.7 m	Step design Steps	Number of steps/rungs 3 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Height 1.34 m	Platform height 680 mm	Base spread 700 mm
Inclination 70 °	Lower outer width 620 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Castor diameter 80 mm	Max. load capacity 150 kg	Design type Freestanding   Single-sided access   With castors	Weight 8.7 kg	Transport dimensions 1442 x 602 x 157 mm, 8.5 kg
Business division MUNK Günzburger Steigtechnik	Order no. 041103	Price € 445.00		

## **Facts**

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep grooved steps and large platform



- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- Four self-locking spring-loaded castors (Ø 80 mm)
- 'safe-cap' ladder joint
- Rigid connection through metal struts detachable on both sides
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Practical storage tray with integrated hooks and tool holders

Step spacing: 235 mm

Ladder inclination: 70°

Maximum load: 150 kg

## Scope of supply

Ladder: 1 x

## Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting



- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures









## Added value

#### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

#### Learn more



#### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



## Spring-loaded castors

- High stability, easy to change position
- Easy to move the ladder when it is set up
- Self-locking
- Also retrofittable and available as a spare part



#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





## Certificates



17KFP0689-04 -Test Certificate "Bauart geprüft"

Valid in



DIN EN 131-3:2007 EK5-AK1 17-02:2017 DIN EN 131-1:2016 DIN EN 131-2:2017 PAK-ANFORDERUNG FÜR GS -ABSCHNITT 3.1(PAH-REQUIREMENT FOR GS - CL. 3.1) AFPS GS 2014:01 PAK



25KFP0048-01 -Test Certificate "Bauart geprüft"

Valid in



DIN EN 131-3:2018 EK5/AK1 17-02.4:2021 DIN EN 131-1:2019 DIN EN 131-2:2017 PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK



# Corporate certifications

## on sustainability criteria









